

## Features and Benefits

### Zero Turn Mowers, Accu-Z®

#### ZT60 & ZT72 Series

Features	Benefits
60" or 72" cutting width	Sized right and priced right for ranch, estate owners, and commercial operators.
Ground speed	Forward 10 mph and reverse 5 mph for high productivity.
Mid-mount deck design	Puts the deck closer to the operator's line of sight for more efficient and precise operation.
Drive tire stance	58.5" width provides for excellent stability over uneven and hilly terrain.
Adjustable steering levers	Comfort Grip Steering levers are designed with a wide range of adjustments to accommodate almost any size of operator.
Premium Drive Tires	24x12.00-12 4ply wide stance premium drive tires provide excellent traction and outstanding side-hill stability.
Floating deck design	Chain suspension design provides excellent flotation over uneven terrain.
Rapid deck height adjustment	Spring loaded and foot operated lever action deck height adjustor with pin locator makes for quick, easy, and precise cutting height adjustments.
Anti-scalp rollers	Four anti-scalp rollers with two located on deck ends and two located toward mid-deck keeps scalping to a minimum.
1/2" to 4 1/2" Cutting height	1" - 5" in 1/4" increments for good cutting height range control.
Front castor action wheels	Two front mounted 13x6.5-6 ribbed tread castor action wheels mounted in heavy duty pivoting castor forks for durable and quick steering response.
Lockable floating front axle.	Floating front axle provides for smoother ride, more uniform cut, and optimal traction capability by keeping all tires equally in contact with the ground over uneven terrain.
High blade tip speed	60" deck has 18,350 fpm & 72" deck has 18,800 fpm for clean cutting.
High lift blades	Heavy-duty high lift blades are made of .20" thick hardened Marbain steel for long life and high-lift design stands grass prior to cutting.
Easy access spindle housings	1" diameter greaseable spindle with ductile iron housings to handle heavy shock loads.
Kevlar drive belts	One hydrostatic drive belt and one deck drive belt made with Kevlar fiber for long belt life.
Electrically released parking brake	Turning the ignition key to off position or spreading both steering levers to open position will automatically engage the automotive style rear drum brakes for added safety and control.
Seat safety interlocks	Rising off of the seat with the blades engaged will stop the blade rotation immediately by shutting the engine down. Engine cannot be started with blade engagement switch on for added margin of safety.
Choice of engines	60" Deck: 24 hp Honda, 25 hp Kawasaki, 27 hp Kohler or 31 hp Kawasaki 72" Deck: 25 hp Kawasaki, 27 hp Kohler or 31 hp Kawasaki
Remote Air Intake	All engines come standard with cyclonic type remote air intake to keep engines running clean and running longer.
Enhanced engine access	Spark plugs, air filter, oil filter, & oil drain are placed easily within reach.
Engine oil cooler	Keeps engine running at peak performance in warm weather conditions.
Hour meter	Actual engine run-time hour meters are standard equipment to maintain service intervals.
Centered Mounted Rear Engine	Engine is mounted in the center and to the rear for better stability, maximum ease of service, and maximum legroom.
Electric start with choke control	Keyed ignition and manual choke control placed and engineered for one-handed starting convenience.
Twin six gallon fuel tanks	12-gallon fuel capacity with sleekly styled twin tanks. Provides plenty of fuel capacity and operating range. Combination tank selector switch and fuel shutoff valve and vented fuel caps placed inboard so they don't get knocked off.

*Designs, specifications, features and information are subject to change without notice.*

## Features and Benefits

### Zero Turn Mowers, Accu-Z®

#### ZT60 & ZT72 Series

<b>Isolated exhaust muffler</b>	Muffler is hidden and tucked down under to reduce noise and provide an added measure of protection against burns.
<b>Completely independent twin hydrostatic drives</b>	Outboard heavy-wall tubular frame members also serve as left and right side independent hydraulic oil reservoirs for the hydrostatic drive motors and pumps on each side of the machine eliminating the possibility of cross-contamination. <sup>50</sup>
<b>Stronger yet cleaner design</b>	Integral frame and hydraulic reservoir construction eliminates the need for cooling fans providing for cleaner and uncluttered component design.
<b>Built in cup holders and ergonomically designed control console</b>	The control console is designed for maximum ease of operation and dual cup holders are standard for operator comfort and convenience.
<b>Hinged Bayonet Mount Seat Platform</b>	Tilts up for easy access to battery and drive components or can be easily removed without tools.
<b>Hinged foot platform</b>	Instantly exposes deck drive components for ease of service.
<b>Comfortable seats</b>	Deluxe Cushion or Molded Vinyl with suspension and adjustable positioning for operator comfort and sustained productivity.
<b>Optional ROPS</b>	Available for added operator protection.

*Designs, specifications, features and information are subject to change without notice.*